



HeadMouse™ for Portables

Product Specifications Sheet



- **Optimized for Portable Computers**
- **Indoor and Outdoor Operation**
- **No Cumbersome Head Mounted Apparatus**
- **Wireless Operation**

All Systems

Operating Wave Band:

- Near Infrared

Computer Interfaces:

- Serial Port, RS-232C, DB-9 connector
- IBM PS/2
- USB (Universal bus)
- ADB (Apple desktop bus)

Wired Switch Interface:

- 1/8" (3.5 mm) microphone jacks

Standard Target:

- Paper thin, 0.25" Diameter, adhesive backing

Portable

Sensor Size:

- Standard - 2.5 x 0.75 x 5 inches
- Miniature - 2.5 x 0.75 x 3.3 inches

Interface Size:

- 7.3 x 5.7 x 1.5 inches

Operating Range:

- 4 to 60 inches

Operating Field-of-View:

- 50° in Azimuth and elevation

Measurement Resolution:

- 0.01 inch typical

Secondary Port:

- Interface for using the computer with a desktop mouse, serial port connection

Input Power:

- 12 or 24 volts DC, designed for direct Connection to a battery (power cables available)
- Supplied with 120 VAC wall transformer (international power options available)

Power Output:

- Conditioned 12 volts for use with available laptop power adapters

Words+, Inc.

www.words-plus.com • info@words-plus.com

1220 W. Avenue J • Lancaster, CA 93534-2902

Phone: 800-869-8521 • Fax: 661-723-2114 • International: 661-723-6523

Note: Specifications are subject to change without prior notice.

Revised 2/19/04